



Bonded Seals British imperial

Thread Diameter M		Size reference	Self-centring reference	D +0.13 -0.00	d +0.13	d ₁	Minimum burst pressure bar
Inch	BSP						
6BA		001		6.35	3.05	4.09/4.16	2150
4BA		002		7.26	4.12	5.26	1570
2BA		003		8.38	5.21	6.35	1360
1/4		004		13.21	6.86	8	2430
1/4		005		13.34	6.99	9.53	1680
5/16		006		13.34	8.31	9.83	1680
5/16		007		14.22	8.64	10.04	1750
3/8	1/8	020	820	15.88	10.37	11.84	1480
0.4		008		18.36	11.26	12.45	1950
7/16		009		19.05	11.69	13.08	1890
1/2	1/4	021	821	20.57	13.74	15.21	1540
9/16		010		22.23	14.86	16.39	1560
0.6		022		22.23	15.83	17.3	1290
5/8		011		25.4	16.51	18.75	1560
	3/8	023	823	23.8	17.28	18.75	1230
11/16		012		25.4	18.16	19.69	1310
3/4		024		26.92	19.69	21.21	1230
13/16	1/2	025	825	28.58	21.54	23.01	1120
7/8	5/8	026	826	31.75	23.49	24.97	1240
15/16		013		33.27	24.26	26.04	1275
1	3/4	027	827	34.93	27.05	28.53	1050
1.1/16		028		28.61	27.82	30.61	1210
1.1/8		014		36.58	29.33	30.86	880
1.3/16	7/8	029	829	38.1	30.81	32.39	860
1.1/4		015		41.4	32.64	35.69	775
1.5/16	1	030	830	42.8	33.89	36.88	780
1.5/16	1	031		42.8	33.89	36.88	780
1.3/8		016		44.45	35.94	38.99	680
1.1/2		017		47.78	38.96	42.04	660
1.5/8	1.1/4	032	832	52.38	42.93	45.93	690
1.3/4		018		57.15	45.34	48.39	870
1.7/8	1.1/2	033	832	58.6	48.44	51.39	690
2		019		63.5	51.69	54.74	780
2.1/8	1.3/4	034	834	69.85	54.89	58.3	950
2.1/4		035		70.36	58.04	61.09	740
	2	036	836	73.03	60.58	63.63	720
2.1/2		037		77.72	64.39	67.44	750
	2.1/4	038	838	79.5	66.68	69.98	670
	2.1/2	039	839	90.17	76.08	79.38	680